

Distributed Systems 600.437 Wireless Mesh Networks

Department of Computer Science
The Johns Hopkins University

Wireless Mesh Networks

Lecture 10

Further reading:

www.dsn.jhu.edu/publications/

The Wireless Revolution

- Wide use of wireless 802.11 networks.
- The norm for Internet connectivity.
- Current practice:
 - The access point paradigm
 - Client – server in nature.
- Academic research:
 - A lot of focus on the ad-hoc paradigm since the 90s
 - Peer 2 peer in nature.
 - The Mesh paradigm introduced in the last few years

What We Were Missing

- The Access Point paradigm is great
 - Until I move away from mine
 - East Coast schools have massive walls ...
- So:
 - Put more access points
 - Connect them all to the Internet
- However:
 - As I move between access points
 - Some interruption in connectivity, potential loss of sessions.
 - Connecting only few of the access points to the Internet could be useful:
 - First responders, lack of infrastructure, etc.
- In parallel: VoIP is becoming popular.
 - Skype.
 - Cell phones with 802.11.

The Mesh Paradigm


- Two classes of participants
 - Mesh nodes and clients
 - Some of the mesh nodes, the **Internet Gateways**, are connected to the Internet.
 - Other mesh nodes forward packets over multiple wireless hops.
 - Clients are mobile
 - Mesh nodes are relatively stationary
- In between the Access Point and the Ad-hoc paradigms
 - Different optimization considerations

Challenges

- Not changing the client
 - No special software or hardware
 - The client should feel as if there is one omni-present access point
- Fast, lossless handoff
 - Handoff between access points fast enough for VoIP and video
 - The responsibility of the mesh and not the client
- Multi-homed mesh environment
 - Multiple Internet gateways
 - Potentially on different networks
 - How to utilize to our advantage
 - Handoff between Internet gateways
 - How to keep connectivity alive on different networks

Introducing SMesh

www.smesh.org



Yair Amir

Fall 09 / Lecture 10

7

Related Work

- **Handoff on Wireless Networks**
 - Mobile IP [C. Perkins, IP Mobility Support, RFC2002, 1996]
 - Handoff in Cellular Wireless Networks [Seshan, Balakrishnan and Katz, Kluwer Journal on Wireless Personal Communications, 1996]
 - An Empirical Analysis of 802.11 Handoff [Mishra, Shin and Arbaugh, SIGCOMM, 2003]
 - SyncScan [Ramani and Savage, INFOCOM, 2005]
- **Wireless Mesh Networks**
 - Metricom Ricochet, MIT Roofnet, Microsoft MCL, Rice TAPS, UCSB/Bell labs MeshCluster, SUNY Stony Brook iMesh, Purdue MAP, UIUC Net-X, Tropos, ...


Yair Amir

Fall 09 / Lecture 10

8

Outline


- Introduction
- Related work
- The SMesh Architecture
 - **Generic overlay network**
 - **Seamless client access**
 - **Multi-homed environment**
- Intra-domain Handoff
 - **How it works**
 - **Experimental results**
- Inter-domain Handoff
 - **How it works**
 - **Experimental results**
- Practical Deployment Considerations
- Summary



The SMesh Architecture



The SMesh Architecture




Yair Amir

Fall 09 / Lecture 10

11

The Spines Messaging System



[DSN03, NOSSDAV05, TOM06]


- Daemons create an overlay network on the fly
- Clients are identified by the IP address of their daemon and a port ID
- Clients feel they are working with UDP and TCP using their IP and port identifiers
- Efficient support for unicast, multicast and anycast

Yair Amir

Fall 09 / Lecture 10

12

The Spines Messaging System



[DSN03, NOSSDAV05, TOM06]

- Daemons create an overlay network on the fly
- Clients are identified by the **IP address** of their daemon and a **port ID**
- Clients feel they are working with UDP and TCP using their IP and port identifiers
- Efficient support for **unicast**, **multicast** and **anycast**

Yair Amir

Fall 09 / Lecture 10

13

Seamless Client Access

- Standard **DHCP** Protocol
- Client always gets the same IP address
 - Assign IP based on **MAC address** (**10.x.y.z**)
- Client routes all packets through a **Virtual Default Gateway**
 - Default Gateway: **10.20.30.40**
 - Netmask: **255.255.255.254**
- Client gets **Gratuitous ARP** to associate Default Gateway IP address with the currently serving access point.




Yair Amir

Fall 09 / Lecture 10

14

A Routing Approach for Lossless Handoff




Yair Amir

Fall 09 / Lecture 10

15

Outline

- Introduction
- Related work
- The SMesh Architecture
 - **Generic overlay network**
 - **Seamless client access**
 - **Multi-homed environment**
- Intra-domain Handoff
 - **How it works**
 - **Experimental results**
- Inter-domain Handoff
 - **How it works**
 - **Experimental results**
- Practical Deployment Considerations
- Summary



Yair Amir

Fall 09 / Lecture 10

16

Intra-Domain Handoff


- Use DHCP to make the client send heartbeats
 - Tuning DHCP T1 and T2 timers.
 - Sending ARP request for client address.
 - Heartbeat is **broadcast** every 2 seconds.
 - Broadcast is less reliable than unicast.
- Nearby access points:
 - Join client **control group**.
 - Constantly measure client connection quality.
 - A decay function based on loss rate of monitored DHCP requests.
 - Signal strength (RSSI) as well.
 - Periodically advertise connection quality on client **control group**.

Fast Lossless Handoff


- Packets to client are sent to client **data group**.
- Access point with best connection quality.
 - Joins client **data group**.
 - Sends **Gratuitous ARP** to mobile client.
- At least one access point in client **data group**.
 - When no longer think it is the best, can request to leave client **data group** by sending request on client **control group**.
 - Can leave only when another access point acknowledges it is the best on client **control group**.
- Therefore, multiple access points in client data group during handoff.
 - **Duplicates are the price of lossless handoff !**

Intra-Domain Handoff

[Mobisys 2006]



Intra-domain Testbed



Test


Full Duplex VoIP
Internet <==> Client

Each Stream

G.711
64 Kbps
160 bytes / 20 ms


Stationary Client: Latency

Internet -> Mobile Client



Packets delayed over 100ms
4 packets


Mobile Client -> Internet



Packets delayed over 100ms
1 packets


Moving Client: Latency

Internet -> Mobile Client



Packets delayed over 100ms
25 packets


Mobile Client -> Internet




Packets delayed over 100ms
13 packets

Moving Client: Duplicates


Internet -> Mobile Client



Intra-domain Testbed




Zooming on the Handoff




Delay Jitter

Internet -> Mobile Client




Mobile Client -> Internet




Delay Jitter between 5% to 95% was < 10ms

Overhead




Outline

- Introduction
- Related work
- The SMesh Architecture
 - **Generic overlay network**
 - **Seamless client access**
 - **Multi-homed environment**
- Intra-domain Handoff
 - **How it works**
 - **Experimental results**
- Inter-domain Handoff
 - **How it works**
 - **Experimental results**
- Practical Deployment Considerations
- Summary




Inter-domain Environment

- Wireless **Auto-discovery** defines wireless topology
- Internet Gateways potentially on **different networks**
- Internet Gateways need to be pre-configured to form an **initial connected graph**
- Internet Gateways advertise their existence on **gateway multicast group**.
- All Internet Gateways eventually form a **fully connected graph**



Inter-Domain Handoff


[WoWMoM 2007]




UDP Inter-domain handoff

- **No SYN Packet** to identify connection establishment
- When hearing a stream packet **without a known owner**, forward to destination **AND** to Internet Gateway Multicast Group
- If a data packet is received on the Internet Gateway Multicast Group, and I am the owner, **forward** the packet to the destination, and **announce** on the Internet Gateway Multicast group that I am the owner
- If **no owner** announcement is heard, forwarding node will **assume** ownership after some time (i.e. 200ms)
- Any non-owner will eventually forward stream packets to owner
- Caveat: **More than one** Internet gateway may assume ownership if stream **fluctuates** between two Internet gateways. We use reverse traffic from destination and lowest IP address to break such ties.

By Product: Optimized P2P Routing



Inter-domain Testbed




Yair Amir

Fall 09 / Lecture 10

33


Inter-domain Handoff Latency

Internet -> Mobile Client



Latency

Mobile Client -> Internet



Latency


Yair Amir

Fall 09 / Lecture 10

34


Inter-domain Handoff Performance

Mobile Client -> Internet



Duplicates


Mobile Client -> Internet



Loss


TCP Throughput

TCP Stream




What about Failures / Crashes?

Mesh Node Failover



Non-Owner Internet Gateway Failover



Yair Amir

Fall 09 / Lecture 10

39

Outline

- Introduction
- Related work
- The SMesh Architecture
 - **Generic overlay network**
 - **Seamless client access**
 - **Multi-homed environment**
- Intra-domain Handoff
 - **How it works**
 - **Experimental results**
- Inter-domain Handoff
 - **How it works**
 - **Experimental results**
- Practical Deployment Considerations
- Summary



Yair Amir

Fall 09 / Lecture 10

40



Low Cost Routers Limitations

- Cost effective deployment requires low-cost mesh nodes.
- Performance bottleneck
 - Overlay routing saturates off-the-shelf, low cost (\$50-\$200) wireless routers
- Solution approach:
 - Overlay architecture for control and monitoring
 - Kernel-level routing for data packets
 - Loadable kernel modules to support overlay multicast routing using kernel **redundant multipath (unicast)** routing.

Performance Impact


[WiMesh 2008]

- Ability to support a much higher number of streams with cheap boxes.
- Overall throughput close to the native box's ability to route.
- In addition:
- Latency reduction of 60% - 75%.



Real-Time Monitoring

www.smesh.org



Yair Amir

Fall 09 / Lecture 10

43

Summary

- Smesh as a wireless mesh network www.smesh.org
 - The first seamless 802.11 mesh with fast handoff
 - Inter-domain handoff for multi-home support
 - Optimized hybrid, wired-wireless routing
- Mesh environments become increasingly complex
 - A few access points with a single Internet connection
 - Inter-domain environments with a few networks and tens of access points
 - Neighborhoods to metropolitan areas ?
- Can it be a reality, and if so, reality for what ?
 - Encouraging signs: first responders, relatively small scale rapid deployments
 - Beyond that?

Yair Amir

Fall 09 / Lecture 10

44

Open Questions

- Overlay networks paradigm
 - Importance as a new paradigm of networking
 - The future of the Internet?
 - Pros and Cons compared with a clean-slate approach.
- Wireless mesh networks
 - Is it here to stay?
 - Will it wash away with better alternatives (cellular, provider-based solutions) ?